

ADDITIVES OLTEC

Dosage	Dosage per 1000 L	Description / Uses
--------	-------------------	--------------------

Additives for soluble oils			
OLTEC Clean PE	0,1 to 0,15%	1 to 1,5 L	Biocide for machining fluids. Fungicidal and bactericidal action. Highly effective for eliminating or preventing yeasts, mould and fungi. Can be used as a preventive or curative treatment
OLTEC Clean BF 15	3 to 6%	30 to 60 L	Treatment before draining of emulsions and semi-synthetic oils, eliminating bacteria, fungi and deposits from tanks. Add 1 day before draining to the product being used. Does not contain boric acid
OLTEC Clean BFW 2	1 to 3%	10 to 30 L	Treatment before draining of emulsions and semi-synthetic oils, eliminating bacteria, fungi and deposits from tanks. Add 1 day before draining to the product being used. Does not contain amines.
Additives for lubricating oils			
OLTEC HC 15	1 to 5%	10 to 50 L	Concentrated cleaner for mineral oil circuits before drainage. Removes gum, varnish and deposits. Treatment of hydraulic oils, gears and coolants.
OLTEC HSC	2 to 8%	20 to 80 L	Anti-wear, anti-seize additive for lubricating oils. Stops seizing, increases oxidation resistance, prevents the accumulation of gum and varnish. Can be used in mineral gear oils and hydraulic oils.